

Hisense



Hi-PRO

Single Zone Ductless Heat Pump

09K-12K BTU

R410A 208-230V/60Hz

10 YEAR
PARTS*
LIMITED WARRANTY


2 YEAR
LABOR*
LIMITED WARRANTY

*: follow instruction on service manual
or from your distributors



Hisense USA Corporation

Specifications



Optional Wired Controller



BTU	9,000	12,000
Capacity (Cooling / Heating) (Btu/h)	9,000 / 9,000	12,000 / 12,000
SEER2 / HSPF2	27.5 / 10	23.5 / 9.8
Sound Pressure (Indoor-Highest, Silent / Outdoor) (dB (A))	Indoor-Highest 42, Silent 28 / Outdoor-55	Indoor-Highest 48, Silent 30 / Outdoor-55
IDU Dimensions (Inch)	34 2/8 x 10 5/8 x 8 3/7	38 4/8 x 12 2/5 x 9 2/7
ODU Dimensions (Inch)	31 7/8 x 23 x 11	31 7/8 x 23 x 11
Std Operating Range (Cooling / Heating)	0°F-115°F / -13°F-75°F	0°F-115°F / -13°F-75°F
Long Pipe Connection (ft)	65ft for length, 16-32ft for height	65ft for length, 16-32ft for height

Standard Features

- SEER2 up to 27.5, HSPF2 up to 10.5, EER2 up to 15.5, ENERGY STAR.
- Xtreme™ Heat: 100% heating: 5°F / 15°C.
- Low temperature heating: -13°F (-25°C).
- Low temperature cooling: 0°F (-18°C).
- Integrated Wi-Fi plus the ConnectLife smart app with Alexa and Google Assistant control put easy operation right at your fingertips.
- Full anti-corrosion protection on outdoor unit for use in seacoast and harsh environments.
- Condenser base pan heater.
- Long connection pipes: 65ft length, up to 33 ft height.
- Vertical and Horizontal Auto Swing louvers.
- Indoor Auto Cleaning mode with FrostClean™ technology.

Optional Features

- Wired control.
- Healthy Filter (Catechin, VC, HEPA, Jasmine aroma filter).



Address: 7310 McGinnis Ferry Rd
Suwanee, GA, 30024, USA
Support Number: 1-888-767-4011
Website: hisensecomfort.com

